

Date	2/12/2016			
Backing	65% Polyester + 35% Cotton			
Coating	100% PVC			
Composition	Coating	380	g/m ²	
	Backing	65	g/m ²	
	Lacquer	5	g/m ²	
	Total	450	g/m²	± 25 g/m²
Thickness		0,85	mm	± 0,10 mm
Tensile strength	ISO 1421 : 1998	length width	>24 >15	daN/ 5 cm daN/ 5 cm
Tear strength	ISO 4674-01 : 2003	length width	>2,0 >2,0	daN daN
Seam resistance	ISO 13936-1 : 2004	length width	>16 >14	daN/ 5cm daN/ 5cm
% Elongation under 30N/5cm	ISO 1421 : 1998	length width	>3 >8	% %
Flex resistance	ISO 5402 1 : 2003			no quality loss after 200000
Combined shear flexing and rubbing	ISO 5981 : 2008			no quality loss after 30000
Abrasion resistance (Martindale)	EN ISO 5470-2 : 2003			>50000
Colour fastness to light	EN ISO 105 B02 : 1994		>5	Servaco R201604577 (10/08/2016)
Flame retardancy	BS 5852 /1 : 1979		Source 0 & 1	WYMTS 77880 (28/07/2016)
Cleaning	We recommend to clean this article with water and soap only. Cleaning products containing alcohol, solvent, bleach or abrasive products can damage this product.			
Disinfecting	On request a list of approved disinfectants can be sent.		takes no responsibility for damage if other products are used.	

Remarks

All the specifications given in this document have been tested in accredited laboratories or in our own laboratory using officially calibrated measuring equipment.

This datasheet is valid for five years after the date of publication. However, we guarantee that the item has been produced with the same ingredients and ISO-9000 procedures were strictly complied with. In the event that any modifications may have been applied during this period, all the properties were retested.

The items delivered comply with the specifications stated in this datasheet. In principle, we do not guarantee properties or characteristics that are not included in it.

Slight colour variations between deliveries are possible. We recommend that you always process items from different deliveries separately. This item complies with the most recent REACH specifications.